

TwistPort™ Adaptor for ePMP™ 2000

ADAPTOR FOR EPMP™ 2000 AP

The TwistPort Adaptor for ePMP™ 2000 AP makes the ePMP™2000 series compatible with all TwistPort™ Antennas. TwistPort™ Adaptors are equipped with our original quick-locking waveguide port. Connecting and disconnecting the ePMP™ 2000 AP into the TwistPort™ Adaptor is very simple and requires no tools.



TECHNICAL DATA

| | |
|--------------------|---|
| Antenna Connection | TwistPort™ - Quick-Locking Waveguide Port |
| Radio Connection | 2x Slide-On RP-SMA |
| Materials | Insert - Aluminium Alloy Adaptor - UV stabilized and weather resistant ABS plastic |
| Flame Rating | UL 94 HB |
| Temperature | -40°C to +60°C (-40°F to +140°F) |
| Wind Survival | 160 km/h |
| Weight | 0.42 Kg / 0.9 lbs – single unit 11.5 Kg / 25.3 lbs – carton (20 units) |
| Single Unit | Retail Box: 10.9 x 9.8 x 5.4 cm |
| 20 Units | Carton Box: 36.1 x 60.9 x 32.5 cm |

PERFORMANCE

| | |
|-----------------|-------------------|
| Frequency Range | 5180 - 6400 MHz |
| Polarization | Dual Linear H + V |
| VSWR Max | 1.8 |
| Impedance | 50 Ohm |

COMPATIBLE WIRELESS PLATFORMS

| | |
|-------------------|------------------------|
| RF elements® | any TwistPort™ Antenna |
| Cambium Networks™ | ePMP™ 2000 AP |

PACKAGE CONTENTS

TwistPort™ Adaptor

PRODUCT DIMENSIONS

